



CLAIMS

1. What I claim as my invention is : ~~radar(s) or Detectable devices equipping at rear vehicle functioning the same way for back driving, Back driving automatic brake system & Automatic braking system~~ used for equipping in all kinds of motor and engine vehicles, automobiles, cars, trucks, buses, vans, trains, tanks, motor vehicles, motorcycles, airplanes, ships etc., including: (re-organized - formerly paragraph 2)

Sensor(s)/radar(s) or detectable devices equipping in the front (top) of vehicle and at its rear (top) part for detecting to detect at certain a distance between two vehicles or obstruction, sensor(s) sending information radar(s) reacting to switch braking unit/motor on to brake the car automatically to stop its running accident once obstruction is detected, (re-organized - formerly paragraph 1)

installation and using of Detectable automatic braking system in all kinds of motor & engine vehicles, automobiles, cars, trucks, buses, vans, trains, motorcycles, tanks, airplanes, ships, etc., wherein using sensor(s) to detect and to respond by detected result to braking unit to perform automatic braking action, (new)

and braking by pressing or pulling manner, new pedals on FIG. 36, FIG. 37, rubber boot, safety covers on FIG. 35, braking positions against extra brake outlets on FIG. 38, automatic braking pedals L23 to L37 for proper automatic braking use without causing movement of vehicle pedal L shown on FIG. 39, FIG. 40, using their main parts wherein or movement of any other equipments, instruments having braking effect; using movement of force by motor, by air, by wind, by spring, by energy, of air hydraulic/oxygen (unit), of air/liquid pump, of cylinder as nut & piston as bolt with induction coils, etc, braking objects including wheels, spindle, axis, rod, oscillator moving frame, bracket drive and any other objects with same effect, using sensors or any other wire/wireless detectable devices; radars, infrared (detector) lenses, detectors, electronic eyes, lighting sensors, motion sensor detectors, sensor video cameras, etc, having heating effect against snow, accessories. (re-organized - formerly claim # 2)

Detectable automatic braking system referring to claim 1, wherein once obstruction being detected, sensor(s)/radar(s) or detectable device(s) automatically reacts braking motor rotating triangle wheel to its edge point pressing at the opposite side of upper pedal to brake, braking locked by iron switches of motor to its inner triangle wheel, brake released by switch device and spring force on FIG. 1, FIG. 2 of triangle wheel structure. (re-organized - formerly claim # 2)

Detectable automatic braking system referring to claim 1, wherein once

obstruction being detected, sensor(s)/radar(s) or detectable device(s) automatically reacts braking motor rotating triangle wheel to its edge point pressing at the opposite side of upper pedal to brake, braking locked by lock device of motor to bracket arm of triangle wheel, brake released by driver's button and spring force on FIG. 3 to FIG. 5 of triangle wheel structure Duo. (re-organized - formerly claim # 2)

Detectable automatic braking system referring to claim 1, wherein once obstruction being detected, sensor(s)/radar(s) or detectable device(s) automatically reacts braking motor rotating triangle wheel to its edge point pressing at the opposite side of upper pedal to brake, braking locked by lock device of motor to bracket arm of wheel, brake released by driver's button and rewind spring or using double spinning motor on FIG. 9, FIG. 10, FIG. 6 of triangle wheel structure Du. (re-organized - formerly claim # 2)

Detectable automatic braking system referring to claim 1, wherein once obstruction being detected, sensor(s)/radar(s) or detectable device(s) automatically reacts brake motor, its axis fixing between center and rim of a round wheel, rotating at wheel summit pushing on pedal part to brake, braking locked by lock device of motor to bracket arm of wheel, brake released by driver's button and rewind spring or using double spinning motor on FIG. 12 of round wheel structure Duo-A. (re-organized - formerly claim # 2)

Detectable automatic braking system referring to claim 1, wherein once obstruction being detected, sensor(s)/radar(s) or detectable device(s) automatically reacts brake motor, its axis fixing between center and rim of a round wheel, rotating at wheel summit pushing on pedal part to brake, braking locked by lock devices of motor to its inner wheel, brake released by driver's contact and spring force on FIG. 14 of round wheel structure Duo-a. (re-organized - formerly claim # 2)

Detectable automatic braking system referring to claim 1, wherein once obstruction being detected, sensor(s)/radar(s) or detectable device(s) automatically reacts brake motor; its toothed spindle engaging through gear-nut of frame screwing out pressing on pedal part to brake, braking locked by lock device, released by driver's button and slotted spindle spring force or spring linked to frame on FIG. 16 of screw & unscrew structure Duo-B. (re-organized - formerly claim # 2)

Detectable automatic braking system referring to claim 1, wherein once obstruction being detected, sensor(s)/radar(s) or detectable device(s) automatically reacts brake motor, its axis engaging a tube outlet of frame with grooved end part rotated by a gear of motor, moving axis pressing on pedal part to brake, braking locked by lock device, released by driver's button and spring on FIG. 18 of axis-gear

structure Duo-C. (re-organized - formerly claim # 2)

Detectable automatic braking system referring to claim 1, wherein once obstruction being detected, sensor(s)/radar(s) or detectable device(s) automatically reacts brake motor, its axis fixing between center and rim of a round wheel with connecting rod, pressing to an extra outlet built from brake original booster/master cylinder to brake, braking locked by lock device and released by driver's button using revert spring force at back spin on FIG. 20 of extra outlet structure Duo-D.
(re-organized - formerly claim # 2)

Detectable automatic braking system referring to claim 1, wherein once obstruction being detected, sensor(s)/radar(s) or detectable device(s) automatically reacts oscillator moving the frame, on which an extra outlet with hose, connecting rod kit in air releasing spring unit placing with ball bearing centered to a wheel, pressing to a rubber cover wheel manufactured as a part of double pulley rotated by car engine to brake, braking locked by lock device, released by driver's contact on FIG. 22 of moving frame structure Duo-E. (re-organized - formerly claim # 2)

Detectable automatic braking system referring to claim 1, wherein once obstruction being detected, sensor(s)/radar(s) or detectable device(s) automatically reacts motor to drive a rectangular bracket pressing on pedal part to brake, braking locked by lock device, released by driver's button and spring force on FIG. 24 of bracket drive structure Duo-F. (re-organized - formerly claim # 2)

Detectable automatic braking system referring to claim 1, wherein once obstruction being detected, sensor(s)/radar(s) or detectable device(s) automatically reacts motor to rotate its bar pressing on pedal part to brake, inner wheel locked by lock device inside motor during braking, released by driver's button and rewind spring on FIG. 26 of direct spin structure Duo-G. (re-organized - formerly claim # 2)

Detectable automatic braking system referring to claim 1, wherein once obstruction being detected, sensor(s)/radar(s) or detectable device(s) automatically reacts motor to rotate its oval wheel pressing on pedal part to brake, wheel locked by lock device, released by driver's button and rewind spring on FIG. 28 of oval wheel structure Duo-H. (re-organized - formerly claim # 2)

Detectable automatic braking system referring to claim 1, wherein once obstruction being detected, sensor(s)/radar(s) or detectable device(s) automatically reacts motor to rotate its hexagonal wheel pressing on pedal part to brake, inner wheel locked by lock device inside motor during braking, released by driver's button and rewind spring on FIG. 30 of hexagonal wheel structure Duo-I. (re-organized -

formerly claim # 2)

Detectable automatic braking system referring to claim 1, wherein once obstruction being detected, sensor(s)/radar(s) or detectable device(s) automatically reacts both functioning of motor braking and pressing button standby of mini-motor which will rotate to draw lock device resulting from earlier pressing action releasing the brake automatically just after radar(s) detecting free, of automatic releasing process. (re-organized - formerly claim # 2)

Detectable automatic braking system referring to claim 1, wherein brake motor be fixed between supporting springs, appropriate motor rotating at a speed to brake a car fast enough to stop its running, if using motor spinning at both sides: one side to brake and the other side to release at low speed replacing spring force, in which switch turning brake motor off prior to braking and locking, lock; pushing a bracket over edge point of a bar/rod under spring force be blockade in device and releasing by cable drawing opposite side of rod on Du7, J2e of FIG. 9 and D7, J2d of FIG. 20, of lock device. (new)

Detectable automatic braking system referring to claim 1, wherein automatic water switch equipped to be connected by raining water between electric wires to turn on second sensor in the front of car for detecting at a longer distance to earlier stop car running on wet, drying water by wind to extinguish the function of second sensor/radar after raining over on FIG. 42 of automatic water switch. (re-organized - formerly claim # 2)

Detectable automatic braking system referring to claim 1, wherein a third sensor/radar be equipped in the front of car to detect to sound sonorous alarm or recorded message to driver at the earliest among these sensors once obstruction detected by this sensor/radar, driver may lower car speed to avert automatic braking, of automatic voice sound. (new)

Detectable automatic braking system referring to claim 1, wherein once obstruction being detected, the third sensor/radar automatically reacts both motor braking and mini-motor drawing to unlock lock device to brake and to release while sensor(s) detecting free to lower car speed safely at a longer distance, or using a second braking unit without lock for third sensor/radar, in which a revert timer be installed to switch off third sensor/radar for certain minutes letting cars approach closer during heavy traffic, of automatic lower speed system. (new)

Detectable automatic braking system referring to claim 1, wherein color signal lamp being "on" showing to driver while entire braking system being "off", driver

may switch off the entire system by a driver's contact when necessary or driver finding impossible to balance his car on ice-covered road if braking operating, in which a thermostat be installed to disconnect color signal lamp in winter snow, of automatic safety system. (new)

2. What I claim as my invention is : Detectable automatic alarm system used for all kinds of motor and engine vehicles, automobiles, cars, trucks, buses, vans, trains, motorcycles, airplanes, ships, etc including: (currently amended)

Small sensor(s)/radar(s) or detectable devices equipping at both sides of a car to sound sonorous alarm or recorded message to driver, indicator showing color signal lamp: right or left side be detected once running cars extremely approaching each other, (re-organized)

and extra sensors/radars or detectable devices equipping on right & left mirrors of cars for back detecting during turning, sonorous (signal) alarm or voice sounding to driver (on indicator) if rear car being detected by radar at a distance while signal lamp being on. (new)

3. What I claim as my invention is : Automatic stop lamp system for traffic light including:

Extra lamp(s) be equipped for traffic light at a position to focus its beam at lighting zone limit on red to stop cars advancing on red that its beam has capacity to react function of Detectable automatic braking system on sensor(s)/radar(s) of front cars. (re-organized)

Detectable automatic braking system referring to claim 1, Detectable automatic alarm system referring to claim 2 and Automatic stop lamp system referring to claim 3 wherein the original elements, composition, function, structures, process of making, contents, illustrations, installation, of the invention, any other structures, modifications, replacement of parts assembling to make up the same systems or to perform similar devices referring to their original fundamentals to the same effect and combining the invention with any other devices or systems using other names are in the scope of the protection of the invention, the invention be used everywhere. (re-organized - formerly claim # 2)